



AccuSpec V8.62

PDP MODEL NOMENCLATURE

1,2,3	4,5,6	7	8	9,10	11,12
PDP	150	A	E	01	30

1,2,3 - Product Type

PDP – Power Vented Propeller Unit

4,5,6 - Furnace Input Rating

150 - 150,000 Btu/hr Input

7 - Heat Exchanger Type

A - Aluminized Steel

8 - Pilot Ignition

E - Intermittent Pilot Ignition

9,10 - Motor and Drive Code (Power Code)

01 - 115v/60Hz/1

11,12 - Control Code Type

30 - Single-Stage, Intermittent Pilot Ignition



AccuSpec V8.62

GENERAL PERFORMANCE DATA



General Performance Data

Model	PDP150
At 0' Elevation	
Btu/Hr. Input	150,000
Btu/Hr. Output	120,000
Entering Airflow (CFM)	2180
Outlet Velocity	931
Air Temp. Rise (°F)	51
Mounting Height (Max Ft.) ¹	16
Heat Throw (Max. Mtg. Ft.) ²	55
Unit Total Power (Amps)	5.0

As Configured at 0-2000 Ft. Elevation

Btu/Hr. Input	150,000
Btu/Hr. Output	120,000
Configured Air Temp Rise (°F)	51

Motor Data

Horse Power	1/8
RPM	1625
Type	
Motor Amps	2.3

Clearances to Combustibles

Top and Bottom	6"
Top of Power Exhauster	6"
Access Side	6"
Non-Access Side	6"
Rear	18"


¹ At 65°F ambient and unit fired at full-rated input. Mounting height as measured from bottom of unit, and without deflector hoods.

² Heat Throws are calculated at 65°F ambient with a 51°F air temperature rise with the unit mounted at a maximum mounting height of 16 feet.



DIMENSIONS – UNIT

Model PDP Dimensions



Model Size Dimensions (inches)

PDP150

A	21
B	35.25
C	22
D	18.5625
E	20
F	12
G	6.5625
H	17.375
J (Round) ¹	
K (Mtg Holes) ²	3/8-16
L ³	35.8125
M	

W	N/A
X	N/A
AA	8
BB	
CC	
DD	2.75
EE	30.5
LL	31.125

Gas Connection ⁴	1/2
Fan Diameter	16
Approx. Shipping Weight	168 lbs.

¹ For some models, this is the dimension of the vent transition outlet supplied with unit.

² PDP 30 through PDP 250 have 2 holes and the level hanging adjustment feature. PDP 300 through PDP 400 have 4 holes.

³ Dimension equals overall plus 6".

⁴ For natural gas; may vary depending on control availability.